



Norsewind - array of wind lidars and meteorological masts offshore

Hasager, Charlotte Bay; Detlef Stein, F. P.; Hagemann, Saskia ; Pena Diaz, Alfredo; Mikkelsen, Torben; Stickland, Matt ; Courtney, Michael; Oldroyd, Andy

Publication date:
2013

[Link back to DTU Orbit](#)

Citation (APA):

Hasager, C. B., Detlef Stein, F. P., Hagemann, S., Pena Diaz, A., Mikkelsen, T., Stickland, M., Courtney, M., & Oldroyd, A. (2013). *Norsewind - array of wind lidars and meteorological masts offshore*. Poster session presented at European Wind Energy Conference & Exhibition 2013, Vienna, Austria.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.


- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

NORSEWIND – ARRAY OF WIND LIDARS AND METEOROLOGICAL MASTS OFFSHORE

Charlotte Hasager (1) F P Detlef Stein (2) Saskia Hagemann (3) Alfredo Peña (1) Torben Mikkelsen (1) Matt Stickland (4) Mike Courtney (1) Andy Oldroyd (5)

(1) DTU Wind Energy, Roskilde, Denmark, (2) GL Garrad Hassan, Hamburg, Germany, (3) Fraunhofer IWES, Kassel, Germany, (4) University of Strathclyde, Glasgow, United Kingdom, (5) Oldbaum Services, Stirling, United Kingdom



Introduction

The FP7 project Norsewind (2008-2012) focused on the offshore study of winds through observations with ground-based wind lidars, meteorological masts and satellite remote sensors, and mesoscale modeling. Some results of the observational array of wind lidars and meteorological masts are presented.



Approach

The approach of the measurement campaign in Norsewind was to cover the Baltic, North and Irish Seas with an array of wind lidars installed on offshore platforms and combine them with existing observations from tall offshore meteorological masts. This resulted in a database with 11 wind lidars and data from around the same number of offshore masts. The work on CFD flow modeling and tunnel experiments on the influence of each of the platforms on the wind lidar observations showed that the measurements are not highly distorted.


High-quality observations of offshore winds at relevant wind turbine heights are challenging to obtain due to logistics and cost. In the Norsewind project an array of wind lidars and meteorological masts were used to assess winds at local points. The major findings from the meteorological observations from masts and wind lidars can be summarized as new knowledge on the vertical wind shear profile offshore. It is generally known that winds in near neutral conditions in the surface boundary layer can be described with the logarithmic profile. The new observations confirmed that this situation is not that frequent and the winds at hub-height (e.g. 100 m) are not always truly within the lowest 10% of the boundary layer where the log profile is valid.

The boundary layer height was not observed in the Norsewind project but obtained from model results from the WRF mesoscale model. Only at some meteorological masts were observations of vertical temperature profiles accessible and that allowed detailed physical investigation of the shear during various conditions. From all wind lidar nodes the shear exponent (alpha) was calculated seasonally, daily and for 12 wind directional bins. Finally, the frequency distribution of alpha for each node was calculated. The relationship between alpha and atmospheric stability, roughness, height and boundary layer height was identified from the dataset.

Map of Northern European Seas and installed instruments.




Background: shear MOST and incl. Peña formulation

Alpha is dependent upon **STABILITY**, roughness, **height** and boundary-layer height

The stability is from very stable black, through neutral green to very unstable magenta. Left graph is without boundary-layer height in formula, right graph include BHL.


Mean stability correction

Atmospheric conditions over the North Sea are on average slightly stable




See Peña and Hahmann, 2012, Wind Energy


Roses of alpha



Distributions of alpha



Distributions of alpha



Conclusions

The vertical wind shear distribution and 'alpha-roses' observed from the array of wind lidars and meteorological masts in the Norsewind project in the Baltic and North Seas are presented.

The commonly adopted offshore vertical wind shear value, alpha 0.2, is valid for a very narrow set of atmospheric and marine conditions. Alpha varies in the marine SBL with atmospheric stability, roughness (as the sea roughness is not constant and increases with wind speed) and height. In offshore conditions the observed alpha values at 100 m AMSL are often within the range -0.2 to 0.8 with a peak within the range 0 to 0.125. Negative values are found both under unstable and stable atmospheric conditions.

References

Peña, A., T. Mikkelsen, S. E. Gryning, C. B. Hasager, A. Hahmann, M. Badger, I. Karagali and M. Courtney, Offshore vertical wind shear, DTU Wind Energy-E-0005(EN), 2012.
Peña and Hahmann 2012 Atmospheric stability and turbulence fluxes at Horns Rev – an intercomparison of sonic, bulk and WRF model data, Wind Energy, 15: 717-731
Further information is available at www.norsewind.eu